

LÁMINAS DECORATIVAS

TECHNICAL DATA SHEET

ITEM	UNIT	STANDARD	METHOD	REMARK
APPEARANCE		CLEAR · FLAT	EYES	
DENSITY	g/cm ³	1.05	ASTM D792	
MELT INDEX	g/10min	2~8	ASTM D1238	
THICKNESS	mm	±5%	CALIBRATOR	
WIDTH	mm	±1	MEASURING TAPE	
LENGTH	mm	0~+5	MEASURING TAPE	
TENSILE STRENGTH	Kg/cm ²	420-460	ASTM D638	
TENSILE ELONGATION	%	2~4	ASTM D638	
FLEXURAL STRENGTH	Kg/cm ²	670~860	ASTM D790	
IZOD IMPACT STRENGTH	Kg-cm/cm	1.6~2	ASTM D256	
HEAT DISTORTION TEMP.	°C		ASTM D648	
UL FLAMMABILITY	-		UL94	
VICAT SOFTENING POINT	°C		ASTM D1525	
1. THIS DOCUMENT IS FOR REFERENCE TO CHECK AND ACCEPT BY BUYER 2. TEST TEMPERATURE IS 23±2°C AND MOISTURE IS 60%±5%RH 3. THE PRODUCT SHOULD BE STORED IN 20°C~30°C ENVIRONMENT, AND DRY PLACE, THE EXPIRE IS ONE YEAR				